

## CUSTOM FIRING

Don't have a kiln or access to one? Bring your work to Georgies for firing. We keep a stable of six kilns in service for our production and your custom firing needs.



- **Georgies fires bisque to cone 04 or glazes to cone 06 or cone 6.**
- Custom firing schedules and temperatures may be available, but only for full kiln loads. Call for details & availability on custom work.
- **Please allow 7-10 business days** turn around time for cone 04, 06 or 6 firing.
- **Firing fees start at \$7.00 minimum** charge, up to \$85.00 for a full kiln load. Filling a Skutt 1227 takes a lot of pieces!
- **All pieces for firing must be completely dry before Firing!** Firing wet pieces may damage your piece, other work in the kiln, and the kiln itself. You may be billed for the cost of kiln repair if that happens.
- Please tell us about any parts that may be missing or broken from your piece when you bring it in.
- **Make sure there's no glaze on the bottom of your Pieces** (dryfooted). We will clean off glaze if necessary, but labor charges will apply.



KM2546

KM2397  
KM2398

KM2480

## SKUTT ENVIRO-VENT

### Kiln manufacturers have always recommended

that firing areas have adequate ventilation. Clay and glass materials contain organic compounds which burn out during the first phase of the firing process. Studies have shown that carbon monoxide emissions from kilns can exceed OSHA Threshold Limit Values during bisque firings in electric kilns. (TLVs define the level to which OSHA believes workers can be exposed day after day without adverse health effects.) Formaldehyde and sulfur dioxide may also be present. Because of these concerns, kiln venting is required by building codes in most areas.

Your work is also likely to suffer if your kiln is not properly vented. Gas contaminants need to be removed and replaced with fresh air. This is especially important with some red, orange, brown and yellow glazes, and with metallic lusters. They need oxygen to achieve the best color results.

Skutt EnviroVents can handle larger kilns or multiple kilns when you use the Dual Exhaust Vent Kit. Use the dual kit to vent a single kiln between 12 and 24 cubic feet in volume, or two kilns up to 12 cubic feet volume each. That's two KM1227s!

The Skutt Enviro-Vent works by drawing air down into the body of the kiln through small holes drilled in the kiln lid. The motor is mounted separately to avoid transmitting vibrations through the kiln body. The Enviro-Vent includes 6 feet of 3" flexible aluminum pipe which joins the spring-loaded plenum cup to the motor. More ducting is available at hardware & home improvement stores.

### Skutt EnviroVent 2

KSVENT .....	(MSRP \$490.00) .....	\$441.00
KS2476 .....	Dual Exhaust Vent Kit .....	\$150.00
	<i>Two 8' hoses, one spring-loaded plenum cup assembly, four hose clamps, one KS2466</i>	
KM2480 .....	Enviro-Link .....	\$105.00
	<i>Control &amp; program your vent directly from the kiln controller with the EnviroLink.</i>	

### Skutt Kiln Accessories

KM1 .....	Wall-Mount Computer Kiln Controller .....	\$828.00
KM2397 .....	Retrofit Lid-Lifter for 12-sd Kilns .....	\$310.00
KM2398 .....	Retrofit Lid-Lifter for 10-sd Kilns .....	\$300.00
	<i>(Lid Lifters now standard on 10 &amp; 12-sided kilns.)</i>	
KM2546 .....	KilnMaster EasyView .....	\$36.00
	<i>(Angled touchpad for easy vision &amp; programming.)</i>	