

CL552 • Trillium Porcelain Slip

Section I: Manufacturer Information

Name:	Georgies Ceramic & Clay Co.	Date Prepared:	1 October 2013
Address:	756 NE Lombard Portland OR 97211	Last Revision:	1 October 2013
Phone:	503.283.1353 or 800.999.2529	Prepared By:	Christy Runyan
Emergency:	503.283.1353 or 800.999.2529		

Section II: Hazardous Ingredients

<u>Hazardous Component</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>	<u>Other Limits Recommended</u>	<u>% Weight</u>
----------------------------	-----------------	------------------	---------------------------------	-----------------

Other Information:

Silica & quartz are harmful only when prolonged and/or excessive respiration of airborne dust occurs. Free quartz can change structure to form TRIDYMITE (above 870 °C) or CRISTOBALITE (over 1470 °C) which have greater health hazards than quartz.

Section III: Physical Data

Boiling Point:	n/a	Vapor Pressure:	n/a
Melting Point:	n/a	Vapor Density:	n/a
Freezing Point:	n/a	Specific Gravity:	2.0
Water solubility:	Negligible	Appearance & Odor:	Grey-white liquid with earthy odor.
pH (Acid/Alkali):	0.0		

Section IV: Fire & Explosion Hazard Data

Flash Point:	Nonflammable.	Extinguishing Media:
Method Used:	n/a	Firefighting Procedure: Will not burn.
UEL Flammable Limit:	n/a	Fire/Explosion Hazards:None.
LEL Flammable Limit:	n/a	

Section V: Reactivity Data

Conditions to Avoid: Free quartz can change structure to form TRIDYMITE (over 870 °C) or CRISTOBALITE (over 1470 °C) which have greater health hazards than quartz.

Chemical Incompatibilities: Hydrofluoric acid dissolves this clay, and the endothermic chemical interaction produces silicon tetrafluoride.

Stability: Stable: hazardous polymerization will not occur.

Disclaimer

Information presented herein has been compiled from sources considered to be dependable, and is accurate and reliable to the best of our knowledge, but is not guaranteed to be so. Because conditions of use of this product are beyond our control, we make no warranties, expressed or implied. This data is provided solely for your consideration and investigation.

All contents copyright 2012
by Georgies Ceramic & Clay Co. Inc.
Permission granted
to reprint this page for your use.

Georgies Ceramic & Clay Co. Inc.
756 NE Lombard • Portland, OR 97211
503.283.1353 • 800.999.2529

Please send comments or questions to
safety@georgies.com.

CL552 • Trillium Porcelain Slip

Section VI: Health Hazard Data

Routes of Entry:	Inhalation, Ingestion, Skin contact
Exposure Symptoms:	Cough, dyspnea, wheeze, impaired pulmonary function, or progressive symptoms if inhaled. Itching on skin contact. May aggravate existing lung or skin conditions.
Health Hazards: (Acute or Chronic)	Prolonged exposure to dust may cause fibrosis of the lung (silicosis), a progressive pulmonary fibrosis. Silicosis is chronic and slow-developing: symptoms may be delayed 10 years or more.
Carcinogenicity:	None reported. (NTP: No. IARC Monograph: No. OSHA regulated: No.)

Section VI-A: Emergency & First Aid Procedures

Dust exposure:	Move to fresh air. Consult physician as necessary.
Eye contact:	Wash eyes immediately with clean water. Consult physician as necessary or if eye irritation persists.
Skin Contact:	Wash with soap & water. Consult physician as necessary or if skin irritation persists.
Ingestion:	

Section VII: Precautions for Safe Handling

If Released or Spilled:	Clean up and collect, minimizing dust generation. Use wet or dustless systems. Causes slippery surfaces when wet.
Waste Disposal:	May be buried in approved land disposal facility in accordance with applicable local, state or federal regulations.
Handling & Storage:	If dust concentrations exceed PEL or TLV limits, use NIOSH-approved dust respirators and goggles. Maintain adequate ventilation in storage areas.
Other Precautions:	Practice good housekeeping. Maintain proper containment or storage of material in sealed or closed containers.

Section VIII: Control Measures

Respiratory Protection:	Up to 5x PEL, use any dust respirator. Up to 10x PEL, use any except single use or 1/4 mask. Up to 50x PEL, use a high-efficiency particulate mask with full face piece as approved by NIOSH.
Ventilation:	We recommend local exhaust, but there are no special requirements or conditions for these systems.
Eye Protection:	Goggles recommended if dust concentration exceeds PEL or TLV.
Protective Gloves:	Optional.
Other PPE:	None required.
Work Practices:	Spills should be cleaned up promptly, and use good housekeeping practices to minimize dust generation.

Disclaimer

Information presented herein has been compiled from sources considered to be dependable, and is accurate and reliable to the best of our knowledge, but is not guaranteed to be so. Because conditions of use of this product are beyond our control, we make no warranties, expressed or implied. This data is provided solely for your consideration and investigation.

All contents copyright 2012
by Georgies Ceramic & Clay Co. Inc.
Permission granted
to reprint this page for your use.

Georgies Ceramic & Clay Co. Inc.
756 NE Lombard • Portland, OR 97211
503.283.1353 • 800.999.2529

Please send comments or questions to
safety@georgies.com.